

Paving Breaker **BV25-1SV**



- **POWERFUL**
- **EFFICIENT**
- **ANTIVIBRATILE**

The perfect paving breaker for hard material

TECHNICAL DATA	
Weight (kg)	28.1
Length (mm)	714
Shank size (mm)	H28X160 H32X160
Nominal pressure (bar)	5,5
Bore(mm)	50
Piston stroke (mm)	156
Blows/min (l/min)	1245
Air consumption (l/min)	1469
Ø hose (mm)	19
Sound level db (A) with muffler (LWAG)	108
Level of vibration (m/s ²): Norm ISO 28927-10 standard. New method of measurement	5.9

Recommended for :
- Heavy demolition works
Ideal work:
- Cut of trenches in asphalt
- Drawing floors
- Hard surfaces
- Tamping-ramming
- Damage

TOOLS

TOOLS	Shank size	Total Length (mm)	Width	Code
Chisel	H28x160	610		12010
Digger steel		355	75	12011
Wide digger steel		350	125	12012
Rammer stem		395		D0000322
Rammer pad			180 (diamètre)	D0006001
Chisel	H32x160	610		12015
Digger steel		355	75	12016
Wide digger steel		350	125	12017
Line oiler				17035

MOIL POINT



NARROW DIGGING CHISEL



WIDE DIGGING CHISEL



RAMMER STEM AND RAMMER PAD

