



LINEAR 430HD 230V/400V



Overview

LINEAR 430HD 230V/400V

cod. 819090

MMA, rectified, electrode welding machine in direct current (DC).

Stepless regulation of welding current.

Use with a wide range of electrodes: rutile, basic, stainless steel, cast iron and aluminium.



3 PH 230V-400V



CE MARKING



EAC CERTIFICATION

Technical data

CODE	CODE 819090	V₀ DC	MAX NO LOAD VOLTAGE 62 V	W^HL	DIMENSIONS 95 x 49 x 68 cm
V_{3PH}	THREE PHASE MAINS VOLTAGE 230 / 400 V	P_{MAX}	MAX ABSORBED POWER 14 kW	kg	WEIGHT 101 kg
F	MAINS FREQUENCY 50 / 60 Hz	P_{60%}	ABSORBED POWER AT 60% 8,4 kW	BAR CODE	EAN CODE 800489795846 0
A_{MIN} / A_{MAX} DC	CURRENT RANGE 80 - 360 A	φ	POWER FACTOR (cosphi) 0,6	Grid	PIECES/PALLET 6 pz/pallet
A_{MAX} 40°C DC	MAX CURRENT DC (EN 60974-1) 325 @ 35 % A	Ø_{DC} MIN/MAX	D. USABLE ELECTRODES IN DC 2 - 6 mm	Grid	PIECES/PALLET - B 3 pz/pallet-B
A_{60% 40°C DC}	DC CURRENT 240 A	IP	PROTECTION DEGREE IP22		